

IN THE CLAIMS:

The following list of claims replaces all other claims:

- Copy*
- 11. (Previously Amended)** A molded article according to claim 25,
wherein the synthetic resin sheet is a transparent or translucent acrylic resin sheet
wherein the outer reinforcing shell layer comprises a thermoplastic resin, a coloring agent
and a filler, and
wherein thermoplastic resin of the outer reinforcing shell layer is mixed with coloring agent
and a filler so that said thermoplastic resin of the outer reinforcing shell layer is colored or patterned.
- 12. (Previously Amended)** A molded article according to claim 25, wherein the synthetic
resin sheet is colored acrylic resin sheet.
- 13. (Previously Amended)** A molded article according to claim 25, wherein said resin of
the outer reinforcing shell layer is glass fiber reinforced acrylonitrile-butadiene-styrene resin or glass
fiber reinforced acrylonitrile-styrene resin or non-reinforced acrylonitrile-butadiene-styrene resin or
non-reinforced acrylonitrile-styrene resin.
- 14. (Previously Amended)** A molded article according to claim 25,
wherein said surface layer is made of one selected from translucent acrylonitrile-butadiene-
styrene resin, translucent acrylonitrile-styrene resin, transparent acrylonitrile-butadiene-styrene resin,
and transparent acrylonitrile-styrene resin;
wherein at least the surface layer is made of translucent acrylonitrile-butadiene-styrene resin

or translucent acrylonitrile-styrene resin; and wherein said molded article is patterned.

15. **(Currently Amended)** A molded article according to claim 25,
wherein the surface layer is provided with a skid-preventing ~~means comprising a textured~~
surface layer texture obtained by subjecting said surface layer to thermoforming twice when said
outer reinforcing shell layer is subjected to an injection molding.

16. **(Previously Amended)** A molded article according to claim 25,
wherein said one selected from acrylonitrile-butadiene-styrene resin and acrylonitrile-styrene
resin is reinforced with glass fiber in which mean length of the glass fiber is 400 to 1000 μm .

17. **(Previously Amended)** A molded article according to claim 25,
wherein said reinforcing layer is formed integrally with a reinforcing rib of increased
thickness in relation to the thickness of the remainder of the outer reinforcing shell layer.

25. **(Currently Amended)** A synthetic resin molded article, comprising:
a surface layer having a front and rear surface; and
an outer reinforcing shell layer coating one surface of said surface layer;
wherein said surface layer is produced by subjecting a synthetic resin sheet to two-step
thermoforming,
and further wherein said outer reinforcing shell layer is obtained by subjecting one selected
from acrylonitrile-butadiene-styrene resin and acrylonitrile-styrene resin to injection molding, at an
injection temperature of about 220 to 290°C injection pressure of about 200 to 1000 kg/cm²,
whereby the surface layer is softened and formed again and simultaneously the surface layer
and outer reinforcing layer are fused.